

# SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

### 1.1 Product identifier

**Product Name: Type RP™  
Rapid Power Electrical Cleaning Wipe**

**Product ID numbers:** RP-1, RP-1L  
RP-XXX (Where XXX is the package code.)

### 1.2 Relevant identified uses of the mixture and uses advised against

**Identified uses:** Utility Cleaner/Degreaser

**List of advices against:** Not applicable.

### 1.3 Details of the supplier of the safety data sheet

**Supplier/Manufacturer:**

**American Polywater Corporation**

11222 - 60th Street North

Stillwater, MN 55082 USA

Tel: 1-651-430-2270

Email: sds@polywater.com

### 1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

## 2. Hazards Identification

### 2.1 Classification of the substance or mixture

**Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).**

Flam Liq 2 H225

Skin Irrit. 2 H315

STOT SE 3 H336

### 2.2 Label elements

**Contains:** 2-methylpentane, Low boiling point naphtha, 1-methoxypropan-2-ol



**Pictograms:**

**Signal word:** Danger

**Hazard Statements:**

H225 Extremely flammable liquid and vapor

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness

**Precautionary Statements:**

P210 Keep away from sparks, flames and hot surfaces. No smoking.

P261 Avoid breathing vapor.

P264 Wash hands thoroughly after handling.

P271	Use in a well-ventilated area.
P280	Wear protective gloves.
P303 + P361 + P353	IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water.
P332 + P313	If skin irritation occurs: get medical attention.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a doctor if you feel unwell.
P370 + P378	In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local and national regulations.

**Notes:** Aspiration classification not applied due to the physical form of the product.

**2.3 Other hazards:** No information available.

**3. Composition/Information on Ingredients**

<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>	<u>GHS/CLP Classification</u>
2-methylpentane	107-83-5	203-523-4	40 - 60%	Flam Liq 2, H225; Asp Tox 1, H304; Skin Irrit 2, H315 STOT SE 3, H336
Low boiling point naphtha	64742-89-8	265-192-2	40 - 60%	Flam Liq 2, H225; Asp Tox 1, H304; Skin Irrit 2, H315 STOT SE 3, H336
1-methoxypropan-2-ol	107-98-2	203-539-1	<10%	Flam Liq 3, H226; STOT SE 3, H336

**4. First Aid Measures**

**4.1 Description of first aid measures**

- Eye Contact:** If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.
- Skin Contact:** Remove contaminated clothing; flush skin thoroughly with water. If irritation occurs, seek medical attention.
- Inhalation (Breathing):** If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention. If breathing is difficult, provide oxygen. If not breathing, give artificial respiration. Seek immediate medical attention.
- Ingestion (Swallowing):** Do not induce vomiting or give anything by mouth unless directed to do so by medical personnel. Get medical attention if symptoms appear.

**4.2 Most important symptoms and effects, both acute and delayed**

Refer to Section 11 for more information.

**4.3 Indication of immediate medical attention and special treatment needed.**

No information available.

**5. Firefighting Measures**

**5.1 Extinguishing media:**

Carbon dioxide, water fog, dry chemical or foam.

**5.2 Special hazards arising from the substance or mixture**

**Hazardous decomposition and by-products:**

Burning generates carbon monoxide, carbon dioxide.

**5.3 Advice for firefighters**

Wear appropriate, protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

**6. Accidental Release Measures**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. For a spill in a confined space, provide mechanical ventilation to disperse or exhaust vapors. For emergency responders: use respiratory protection: half-face or full-face respirator with filter(s) for organic vapor for spills in a confined space. Chemical goggles are recommended if splashes or contact with eyes is possible. For small spills: normal antistatic work clothes are usually adequate.

**6.2 Environmental precautions:**

Avoid release to the environment.

**6.3 Methods materials for containment and cleaning up:**

Collect towel and absorb any excess material with sand or absorbents.

**6.4 Reference to other sections:**

Refer to Sections 4, 5, 8, and 13 for more information.

**7. Handling and Storage**

**7.1 Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use only outdoors or in a well-ventilated area. For industrial or professional use only.

**7.2 Conditions for safe storage, including incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

**7.3 Specific end uses**

See technical data sheet on this product for further information.

**8. Exposure Controls / Personal Protection**

**8.1 Control parameters**

**Exposure limits and recommendations:**

**2-Methylpentane (107-83-5)**

Country/Source	Long-term exposure limit – 8 hr TWA	Short-term exposure limit – 15 min
USA, ACGIH TWA*	500 ppm	1000 ppm
USA, OSHA PEL	500 ppm	1000 ppm
USA, NIOSH	100 ppm / 1800 mg/m <sup>3</sup>	--
Alberta, OEL	500 ppm / 1760 mg/m <sup>3</sup>	1000 ppm / 3500 mg/m <sup>3</sup>

**Low boiling point naphtha (64742-89-8)**

No information available

**1-Methoxypropane-2-ol (107-98-2)**

Country/Source	Long-term exposure limit – 8 hr TWA	Short-term exposure limit – 15 min
USA, ACGIH TWA*	100 ppm	150 ppm
Alberta, OEL	100 ppm / 369 mg/m <sup>3</sup>	150 ppm / 553 mg/m <sup>3</sup>
British Columbia, OEL	50 ppm	75 ppm

Ontario, OEL	50 ppm	100 ppm
Quebec, OEL	100 ppm / 369 mg/m <sup>3</sup>	150 ppm / 553 mg/m <sup>3</sup>
Saskatchewan, OEL	100 ppm	150 ppm

*\* Manitoba, Newfoundland and Labrador, Nova Scotia, and Prince Edward Island are all based on the current ACGIH TLVs. British Columbia is based on current ACGIH TLV unless otherwise noted. New Brunswick is based on an older version ACGIH. Nunavet and Northwest Territories are based heavily on current ACGIH TLVs.*

**8.2 Exposure controls**

**Respiratory protection:**

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

**Protective gloves:**

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Suggested Material: Nitrile Rubber  
For short term contact (<15 minutes), splashes use 0.2 mm. For full contact use

Suggested Thickness: 0.4 mm

Exact break-through time has not been determined. Guidance is based on similar chemistry/material.

Maximum wearing time should be determined based on 50 % of the penetration time determined by EN 374 part III.

**Eye protection:**

Safety glasses recommended.

**Other protective equipment:**

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

**9. Physical and Chemical**

**9.1 Information of basic physical and chemical properties**

<b>Appearance:</b>	Clear, colorless liquid; mild odor.
<b>Odor threshold:</b>	Not available
<b>pH:</b>	Does not apply
<b>Freezing point:</b>	Not available
<b>Boiling point:</b>	144°F / 62°C (initial)
<b>Flash point:</b>	19°F / -7°C (TCC)
<b>Evaporation rate:</b>	>2 (n-butyl acetate = 1)
<b>Flammability (solid, gas):</b>	Not applicable to liquids
<b>Flammability limits:</b>	<b>LEL:</b> 1.2%
<b>Vapor pressure:</b>	Not available
<b>Vapor density (Air = 1):</b>	>1 (Air = 1)
<b>Specific gravity (H<sub>2</sub>O = 1):</b>	0.72
<b>Solubility in water:</b>	Not available
<b>Coefficient of Water/Oil Distribution:</b>	Not available
<b>Auto-ignition temperature:</b>	Not available
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	Not available

**9.2 Other Information**

<b>Volatiles (Weight %):</b>	100%
<b>VOC Content:</b>	720 g/l

**10. Stability and Reactivity****10.1 Reactivity:**

See remaining headings in Section 10.

**10.2 Chemical stability:**

Stable

**10.3 Possibility of hazardous reactions:**

None known.

**10.4 Conditions to avoid:**

Avoid heat, flame, and sparks.

**10.5 Incompatible materials :**

Strong oxidizing agents.

**10.6 Hazardous decomposition products:**

Carbon dioxide, carbon monoxide.

**11. Toxicological Information****11.1 Information on toxicological effects:****Acute toxicity****Eye contact:**

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

**Skin contact:**

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

**Irritation and Sensitization Potential:**

Product may be irritating to skin and eyes. It is not a sensitizer.

**Inhalation (Breathing):**

Concentrated solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

**Ingestion:**

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

**Toxicity to Animals:**

2-methylpentane	No Data Available
Low boiling point naphtha	LD <sub>50</sub> (oral rat) >5,000 mg/kg LD <sub>50</sub> (dermal rabbit) >2,000 mg/kg Rabbit 4 hr exposure: Irritating to skin, irritating to eyes
1-methoxypropan-2-ol	LD <sub>50</sub> (oral rat) 6,100 mg/kg LD <sub>50</sub> (dermal rabbit) 13,000 mg/kg LC <sub>50</sub> (inhl rat) >6 mg/l

**Chronic Exposure:**

**Reproductive Toxicity:** No data available.

**Mutagenicity:** No data available

**Teratogenicity:** No data available

**Specific Target Organ Toxicity (STOT)** No end point data.

**Toxicologically Synergistic Products:** Not available.

**Carcinogenic Status:**

- IARC** No components of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC.
- OSHA** No components of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
- NTP** No components of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

## 12. Ecological Information

### 12.1 Ecotoxicity:

#### Aquatic Toxicity:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2-methylpentane

No Data Available

Low boiling point naphtha

96 h LC<sub>50</sub> Oncorhynchus mykiss (Rainbow Trout) 8.2 mg/l

48 h EC<sub>50</sub> Daphnia magna (water flea) 4.5 mg/l

96 h EC<sub>50</sub> Pseudokirchneriella subcapitata (green algae) 3.7 mg/l

1-methoxypropan-2-ol

96 h LC<sub>50</sub> Pimephales promelas (Fathead Minnow) 20,800 mg/l

48 h LC<sub>50</sub> Daphnia magna (water flea) 23,300 mg/l

7 d EC<sub>50</sub> Pseudokirchneriella subcapitata (green algae) > 1000 mg/l

### 12.2 Persistence and degradability:

Expected to be biodegradable

Low boiling point naphtha

77% biodegradable, 28 d exposure time, method: OECD 301E

1-methoxypropan-2-ol

96% biodegradable, 28 d exposure time, method: OECD 301E

### 12.3 Bioaccumulation potential:

No information available

### 12.4 Mobility in soil:

No information available

### 12.5 Results of PBT and vPvB Assessment:

This product is not, nor does it contain a substance that is a PBT or vPvB.

### 12.6 Other adverse effects:

None known.

## 13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

## 14. Transport Information

### US DOT Domestic Ground Transportation:

Not Regulated (See Special Provision 47).

### UN Number:

3175

### UN Proper shipping name:

Solids Containing Flammable Liquid, N.O.S., (Contains: 2-methylpentane, Low boiling point naphtha)

### Transport hazard class(es):

Class 4.1

### Packing group:

II

### Environmental hazards:

None known

### Special precautions:

None known

### ICAO/IATA-DGR:

Not Regulated (See Special Provision A46)

### IMDG:

Not Regulated (See Special Provision 216)

## 15. Regulatory Information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### USA Federal and State

All components are listed on the TSCA inventory.

**Hazard Categories for SARA Section 311/312 Reporting**

Acute  
Yes

Chronic  
Yes

Fire  
Yes

Pressure  
No

Reactive  
No

**Components**

Components are not affected by these Superfund regulations.

**CERCLA/SARA Sec 302**

**Hazardous Substance RQ**

**EHS TPQ**

**SARA Sec. 313**

**Toxic Release**

**NFPA Ratings:**  
Health: 2  
Fire: 3  
Reactivity: 0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

**European Union**

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list ≥ 0.1% SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

**Canada**

All components are listed on the DSL inventory. This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

**Australia**

All components are listed on the AICS. Hazardous according to criteria of NOHSC Australia.

**15.2 Chemical Safety Assessment**

No chemical safety assessment has been carried out for the mixture by the supplier

**16. Other Information**

**Abbreviations and acronyms:**

- OSHA = Occupational Safety and Health Administration
- CLP = Classification, Labeling and Packaging Regulation
- STOT = Specific Target Organ Toxicity
- LD<sub>50</sub> = Median Lethal Dose
- DNEL = Derived No Effect Level
- ACGIH = American Conference of Governmental Industrial Hygienists
- TSCA = Toxic Substances Control Act (USA)
- DSL = Domestic Substances List (Canada)
- AICS = Australian Inventory of Chemical Substances

**Revision Date:** August 4, 2017  
**Revision Number:** 2 NA  
**Supersedes:** April 23, 2015  
**Other:** Not Applicable  
**Indication of Changes:** Updated sections 1, 2, 8, 16; new precaution statements, additional exposure data, general formatting.  
 Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Canada HPR (SOR/2015-17)(WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.