

MATERIAL SAFETY DATA SHEET

TUF-CUT™ THREADING OIL- DARK

SECTION I – PRODUCT INFORMATION

Distributor's name: Allied Rubber & Gasket Company, Inc. – ARGCO
2610 Commerce Way
Vista, Ca 92081

In case of emergency: Contact your local poison control center
For information call: (800) 854-1015
Date prepared: 3/29/2010
Product name: Tuf-Cut™ Threading Oil

SECTION II – INGREDIENTS/IDENTITY INFORMATION

CAS #: None
Contains components listed with TSCA

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

| | | | |
|--------------------------------------|------------------------------|---------------------------------|---------------------|
| <u>Boiling Point:</u> | 760MM HG F, C | <u>Specific Gravity:</u> | (H2O=1) 0.88 |
| <u>Vapor Pressure:</u> | (mm Hg @ 20C) ND | <u>Melting Point:</u> | N/A |
| <u>Vapor Density:</u> | ND | <u>Evaporation Rate:</u> | (Butyl Acetate=1)>1 |
| <u>Solubility in Water:</u> | Negligible | <u>pH:</u> | ND/A |
| <u>Appearance & Odor:</u> | Dark Oil/Characteristic Odor | | |

SECTION IV – FIRE & EXPLOSION DATA

Flash Point: >330F (COC)
Flammable Limits: LEL ND UEL ND
Extinguishing Media: Dry Chemical, Foam, CO2
Special Fire Fighting Procedure: Fire fighters should wear self –contained breathing apparatus.
Unusual Fire & Explosion Hazards: None

SECTION V – REACTIVITY DATA

Stability: Stable
Incompatibility (material to avoid): Strong oxidizing agents
Hazardous Decomposition or Byproducts: CO, CO2
Hazardous Polymerization: Will not occur
Conditions to Avoid: None

SECTION VI – HEALTH HAZARD DATA

Routes of Entry: Inhalation, Skin, Ingestion
Health Hazard (acute & chronic): No known acute health hazards

Target organs (oil mist): Prolonged or frequent use may cause mild skin and eye irritation
Respiratory system & skin
Carcinogenicity: None known
Sign & Symptoms of Overexposure: Possible red and/or itching skin due to overexposure
Medical Conditions generally aggravated by Exposure: None known

Emergency & First Aid Procedures:

Eye Contact: Flush with water for at least 15 minutes and seek medical attention immediately.

Skin Contact: Wash with soap and water.

Inhalation: If a person breathes in large amounts of this product, move the exposed person to fresh air at once.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING & USE

Steps to be Taken in Case Material is Released or Spilled:

Extinguish all flames in area. Dike spill and soak up on inert absorbent material.

Waste Disposal Method:

Follow governmental and corporate regulations for lubricating oil.

Precautions to be Taken in Handling & Storage:

Store containers closed, away from extreme heat & open flames.

Other Precautions:

Use good personal hygiene. For industrial use only. Avoid breathing mist.

SECTION VIII – CONTROL MEASURES

NFPA Health – 0 Flammability – 1 Reactivity – 0 Personal Protection – 0

Respiratory Protection (specific type):

If ventilation equipment is not sufficient to keep airborne concentration below exposure limits, a NIOSH approved respirator should be worn.

Ventilation:

Local exhaust, mechanical.

Protective Gloves:

Oil-impermeable.

SECTION VIII – CONTROL MEASURES - Continued

Eye Protection:

Safety glasses.

Other Protective Clothing:

None

Work/Hygienic Practices:

Laundry soiled clothing before reuse. Keep work area neat. Clean up spills immediately. Practice good personal hygiene.

PLEASE NOTE: If you repackage or otherwise redistribute this product to industrial customers, a notice similar to this one should be sent to that customer.

Disclaimer

The information contained herein is accurate and reliable as of the date issued to the best of the manufacturer's knowledge. ARGCO doesn't warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising from the use thereof. It is the user's responsibility to satisfy itself that the information offered for its consideration is suitable for its particular use.

END OF MATERIAL SAFETY DATA SHEET